

Refrigerated and ventilated display case on refrigerated tank - 3 shelves

- ▶ Stainless steel top AISI 304, th. 12/10
- ▶ Refrigerated laminar airflow in the tank and on all shelves
- ▶ Shelves made entirely of glass to enhance the display area
- ► Stainless steel height-adjustable blind bottoms (useful height 30-150 mm)
- ▶ Evaporator with anti-corrosion coating, which can be lifted to easily clean the wel
- Condensed water drain on bottom (evaporation kit on request)
- Insulation by high density expanded polyurethane without C.F.C. and H.C.F.C.
- With condensing unit
- ▶ Digital control system for temperature adjustment and defrosting
- Sliding doors on operator side to easily refill the display
- LED lighting on the ceiling

SPECIFICATION	2 GN1/1
External dimensions [mm] LxP	800x760
Well dimensions [mm] LvxPvxHv	650x510x30/150
Capacity GN 1/1 containers	2 GN1/1
Temperature [C°] closed, w/flaps	-1/+5*
Temperature [C°] w/curtain	-1/+7**
Refrigerant gas	R404A
Cooling power at -10°C [W]	750
Total power [Kw]	0,8
Supply voltage (50Hz)	230V 1F+N
Diameter inlet gas pipe [mm]	6
Diameter outlet gas pipe [mm]	10





Model 804855 shown on stand (included at no charge)





